



# ULTRA BUGGY®

TRACKED 2500-T

Toro is redefined the material handling category with the introduction of the tracked Ultra Buggy. With controls that are intuitive and easy to use, superior traction and maneuverability, high weight carrying capacity, and a powerful engine, the Toro tracked Ultra Buggy represents the ultimate in productivity and jobsite efficiency. The power, productivity, durability, ease-of-use and service-friendly design all add up to a better ROI.

## FEATURES

### PRODUCTIVITY

- Responsiveness of controls results in great maneuverability, particularly in confined areas
- High weight carrying capacity and the powerful engine rises to the challenge at even the most intimidating jobsites
- Ideal transport speed means getting the job done on time
- Large fuel tank capacity allows for all day productivity

### EASY-TO-USE

- The traction controls are easy to learn, effortless to operate, smooth and responsive
- The unique dump switch is linked to the movement of the traction control and is always near the operator's thumb for easy access
- Auto-return dump feature ensures the tub automatically returns to resting position so the operator can quickly focus on obtaining the next load of concrete
- Suspended, ride-on platform results in less operator fatigue, folds up for ease of trailering

### DURABLE & POWERFUL

- Powerful and proven 25 HP\* Kohler Confidant engine
- The machine and its components have been designed and tested to achieve a 2,500 lb carrying capacity, which improves durability and longevity
- Rugged aramid corde reinforced tracks lead to superior traction over slopes and various terrain

### SERVICEABILITY

- Belt, hydros and battery are all easily accessible
- Engine compartment is designed so routine maintenance can be accomplished efficiently
- Notably fewer hoses and fittings compared to other machines means less service time and cost

### SPECIFICATIONS

Ultra Buggy 2500-T (model 68138)	
Engine	25hp* Kohler® Confidant
Dimensions (LxWxH)	
Platform down	109.5" x 35.5" x 47.7" (278.1 x 90.2 x 121.2 cm)
Platform up	95.5" x 35.5" x 47.7" (242.6 x 90.2 x 121.2 cm)
Weight	1,619 lbs
Tub Volume	16 ft³
Max Load Capacity	2,500 lbs.
Speed	0 - 6 mph forward 0 - 3 mph reverse
Fuel Capacity	10 gallons



\*The gross horsepower of this engine was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual horsepower on this class of product will be significantly lower.