

GRAPPLES

V40 SKELETON GRAPPLE

Available widths 66", 72" & 84"

Open-sided design for hauling brush, logs, and debris.



35.2" JAW OPENING	~8.5" TINE SPACING	< 2400 LB LOADER OPERATING CAP.
--------------------------------	---------------------------------	---

1. EVERY TINE IS MADE FROM ONE PIECE OF STEEL FOR MAXIMUM RIGIDITY
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON HINGES

Known clearance issue on John Deere® 330G, 331G, 332G and 333G.

	MODEL BSGV66	BSGV72	BSGV84
Overall Width (in.)	67.5	73.5	85.5
Height: Overall / Bucket (in.)	26.5 / 20.3		
Overall Depth (in.)	36.9		
Number of Tines (w/ sides)	8	9	10
Space Between Tines (in.)	8.9	8.5	8.9
Tine Thickness (in.)	0.5'		
Cylinder Bore / Stroke (in.)	2.0 / 8.375		
Cylinder Pins / Hinge Pins Dia. (in.)	1.25 / 1.25		
Grapple Jaw Opening (in.)	35.2		
Approximate Weight (in.)	780	815	860
Recommended Loader Capacity	Less than 2400 lbs		

¹Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).

V50 SKELETON GRAPPLE

Available widths 60", 66", 72", 78", 84" & 90"

One of the most popular and versatile Virnig grapples. Handles brush, logs, and debris.



0.5" GRADE 80 STEEL TINES	36.1" JAW OPENING	5.5" TINE SPACING	> 1500 LB LOADER OPERATING CAP.
-------------------------------------	--------------------------------	--------------------------------	---

1. EVERY TINE IS MADE FROM ONE PIECE OF STEEL FOR MAXIMUM RIGIDITY
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS
3. STANDARD WITH CYLINDER GUARDS

	MODEL SGV60	SGV66	SGV72	SGV78	SGV84	SGV90
Overall Width (in.)	61.5	67.5	73.5	79.5	85.5	91.5
Height: Overall/Bucket (in.)	27.8 / 21.3					
Overall Depth (in.)	39.9					
Number of Tines (w/ sides)	11	12	13	14	15	16
Space Between Tines (in.)	5.5					
Tine Thickness (in.)	0.5'					
Cylinder Bore / Stroke (in.)	2.0 / 8.375					
Cylinder Pins / Hinge Pins Dia. (in.)	1.25 / 1.563					
Grapple Jaw Opening (in.)	36.1					
Approx. Weight (lbs)	815	850	885	920	955	990
Recommended Loader Capacity	Greater than 1500 lbs					

¹Material is Grade 80 Plate (80,000 PSI Minimum Yield Strength).