

BRUSH CUTTERS

V50 OPEN FRONT ROTARY BRUSH CUTTER

Available widths 66", 72" & 78" & 84"

Cuts up to 6" diameter trees, and exposed blades allow faster cutting for a maintained finish.



E·T·O·N

Char-Lynn

Do not operate rotary brush cutter without a shatterproof cab on loader.

| | | | | |
|-----------------------------|--|--|---|--|
| 6.0" CUT CAPACITY | 66" - 84" FOUR CUT WIDTHS | 14-42 GPM FOUR MOTOR OPTIONS STANDARD & HIGH FLOW | UP TO 275 LB FLYWHEEL WEIGHT | UP TO 1770 LB OVERALL WEIGHT |
|-----------------------------|--|--|---|--|

DETAIL UNDER DECK
(72" MODEL)



BRUSH CUTTERS



- 1. DIRECT DRIVE EATON® MOTOR WITH RELIEF VALVES
- 2. HYDRAULIC BRAKING STOPS FLYWHEEL WITHIN 10 SECONDS
- 3. STANDARD MOTOR GUARD & SPINDLE GUARD
- 4. ROUNDED FLYWHEEL WITH 3 DOUBLE-SIDED BLADES BOUNCES OFF STUMPS
- 5. REPLACEABLE FRONT SKID SHOES

| MODEL | RBV66-O | RBV72-O | RBV78-O | RBV84-O |
|----------------------------------|-------------------|--|-------------------|-------------------|
| Cut Width (in.) | 66.0 | 72.0 | 78.0 | 84.0 |
| Overall Width (in.) | 72.0 | 78.0 | 84.0 | 90.0 |
| Overall Height (in.) | | | 21.4 | |
| Overall Depth (in.) | 76.3 | 82.3 | 88.3 | 94.3 |
| Deck Height (in.) | | | 7.3 | |
| Push Bar Height (in.) | | | 20.4 | |
| Minimum Cut Height (in.) | | | 2.0 | |
| Cutting Capacity, Diameter (in.) | | | 6.0 | |
| Deck Thickness: Top / Side (in.) | | | 0.25 ¹ | |
| Recommended Flow Rate (GPM) | | 14 – 25 Standard Flow, 25 – 42 High Flow | | |
| Approximate Weight (lbs) | 1465 ² | 1550 ² | 1625 ² | 1700 ² |
| Recommended Loader Capacity | | Greater than 1500 lbs | | |

¹Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).
²High Flow Motor Options Add Approximately 70 lbs to Model Weight.