

BROOMS

PICK-UP BROOM

Available widths 60", 72" & 84"

Direct drive Eaton® motor and intelligent design ensure years of performance.



EATON

Char-Lynn

Standard with 26" diameter poly/wire wafers; all-poly wafers also available.

15-25 GPM
RECOMMENDED
FLOW RATE

DIRECT DRIVE MOTOR
WITH RELIEF VALVE PROTECTION

GREATER THAN
1500 LB
LOADER OPERATING CAPACITY



OPTION: LOW PROFILE WATER KIT

40-gallon tank provides 25 minutes of continuous runtime and drains from the bottom to use full capacity.

*60" model uses different, non-low profile tank. Contact Virnig for more details.




**OPTION:
GUTTER BRUSH**


Increases cleaning width by 12" and allows sweeping next to curbs and buildings.



SHOWN WITH LOW PROFILE WATER KIT OPTION



1. RECESSED & GUARDED MOTOR



2. OVERSIZED 2" GREASEABLE BEARING



3. PIN ADJUSTMENT SYSTEM TO QUICKLY SET BRISTLE HEIGHT

4. HD BUCKET WITH WEAR BARS & BOLT-ON EDGE

5. REPLACE WAFERS EASILY WITHOUT DISCONNECTING HOSES. STANDARD WITH POLY/WIRE WAFERS.

MODEL	PUB60	PUB72	PUB84
Sweeping Width (in.)	60.0	72.0	84.0
Overall Width (in.)	67.3	79.3	91.3
Overall Height (in.)		31.3	
Overall Depth (in.)		62.4	
Number of 26 Inch Diameter Wafers	29	35	41
Recommended Flow Rate (GPM)		15-25 Standard Flow Only	
Approximate Weight (lbs)	990	1120	1250
Recommended Loader Capacity		Greater than 1500 lbs ¹	

¹Recommended Loader Capacity with Water Kit installed is 1800 lbs.